



Enjoying the sounds of nature Feeling the outstanding elegance



Profesional Class

"H" Power Amplifier



T SERIES

Switch Power Amplifier



T-SERIES Switch Power Amplifier

DISCRIPTION 產品描述

L-Solution T series switch power amplifier deliver high performance and quality at an astonishingly affordable price. Designed for professional use in touring racks as well as for fixed installation.

Engineered for utmost ease of use, these amps offer connection options XLR inputs for patching in signals as well as Speakon ports for connecting speaker systems, What's more, their extensive protective circuits ensure reliable, safe operation. applications widely.

鑄之迅T系列開關電源功放傳承卓越性能、高品質和超乎想象的高性價比。為大型專業演出和固定安裝的音響系統而誕生。為了達到最佳的使用效果，所有的T系列開關電源功放都配備有相應的XLR信號輸入和Speakon連接座。最重要的是該系列產品內置有持續保護電路，確保設備長時間的安全、穩定工作。

Features 產品特征

- Switch power amplifier
- 2,4 channels
- Powerful output
- Light weight
- Compact 2 U
- Overheat, clipping, overload, short circuit protection and soft start
- Perfect limit processor
- Available on 2 ohm
- Operation mode switchable (Stereo,Bridge and Mono)
- 開關電源功放
- 2/4 通道
- 體積小，重量輕
- 緊湊2U機箱
- 短路、斷路、直流電壓、過熱、射頻、超低頻保護
- 完美壓限處理
- 可2歐負載工作

SPECIFICATIONS 產品參數

Model:	型號	T215	T216	T240	T413
Power RMS @ 8 ohms:	8Ω立體聲功率:	2x1450W	2x1650W	2x2350W	4x1300W
Power RMS @ 4 ohms:	4Ω立體聲功率:	2x2800W	2x3000W	2x4400W	4x2100W
Power RMS @ 2 ohms:	2Ω立體聲功率:	2x3500W	2x4500W	2x7000W	4x2500W
Power Bridged @ 8 ohms:	8Ω橋接功率:	5600W	6000W	8800W	2x4200W
Power Bridged @ 4 ohms:	4Ω橋接功率:	7000W	9000W	14000W	2x5000W
Frequency Response:	頻率響應:	20Hz-34KHz			
THD @ 1 kHz:	總諧波失真:	<0.1%			
S/N Ratio:	信噪比:	>112 dB			
Channel Separation(Crosstalk)@1kHz:	通道分離度(串音):	>70 dB			
Cooling:	冷卻方式:	Front-to-rear air flow, temperature controlled speed fan			
Signal Input:	信號輸入:	2x XLR			
Signal Output:	信號輸出:	2x XLR			
Input impedance:	輸入阻抗:	20K ohms			
Output Connector:	輸出連接器:	4x Speakon N4			
TourClass Protection:	功放保護功能:	ACL, IGM, Auto Ramp, short circuit, DC voltage, turn-on/off transient, Current inrush, sub/ultrasonic input			
Operating Voltage, 230V/115Vnominal:	工作電壓:	130-265 V / 65-135 V selectable			
Voltage Gain (dB):	電壓增益:	23, 26, 29, 32, 35, 38, 41, 44 dB selectable			
Level adjustment (per CH.):	電平調節:	Front-panel potentiometer, 31 position detente from 1 nF to 0 dB			
Installation Standard:	機箱規格:	2 U			
Product Dimensions :	產品尺寸:	483x88x396mm			
N.W./G.W.:	淨重/毛重:	12KG/13.4KG Carton (1 PC/CTN)			



Q-SERIES Digital Amplifier

DESCRIPTION 產品描述

L-solution Q series digital amplifier shows its high-performance with wonderful quality by the attractive price. Designed for professional use in all the events to reach the perfect effects. Compared with normal amplifier, it is certainly thinner, smaller and more accurate, which is easier to carry and ship. The extensive protective circuits even ensure safe operation.

鑄之迅Q系列數字功放以合理優惠的價格展示了它卓越出眾的性能和極其出色的音質。專為大型專業演出而設計，以達到理想效果。相比其他普通的功放，Q系列數字功放機身更薄，體積更小，數據更準確，使其更加容易運送。內置保護電路功能確保設備能安全穩定地工作。

Features 產品特征

- 2/4 Channels input and output
- Available setting independently on
- Thin
- Have protect circuit function
- 兩/四路音源輸入輸出
- 每路音量獨立調節
- 輕薄機身
- 有保護電路功能

SPECIFICATIONS 產品參數

Model:	型號	Q1	Q3	Q5	Q7
Power RMS @ 8 ohms:	8Ω立體聲功率:	4x600W	4x900W	4x1300W	4x2100W
Power RMS @ 4 ohms:	4Ω立體聲功率:	4x900W	4x1350W	4x2100W	4x3150W
Power RMS @ 2 ohms:	2Ω立體聲功率:	NA	NA	NA	NA
Power Bridged @ 8 ohms:	8Ω橋接功率:	NA	NA	NA	NA
Power Bridged @ 4 ohms:	4Ω橋接功率:	NA	NA	NA	NA
Frequency Response:	頻率響應:	20Hz-34KHz			
THD @ 1 kHz:	總諧波失真:	<0.1%			
S/N Ratio:	信噪比:	>112 dB			
Channel Separation(Crosstalk)@1kHz:	通道分離度(串音):	>70 dB			
Cooling:	冷卻方式:	Front-to-rear air flow, temperature controlled speed fan			
Signal Input:	信號輸入:	2x XLR			
Signal Output:	信號輸出:	2x XLR			
Input impedance:	輸入阻抗:	20K ohms			
Output Connector:	輸出連接器:	4x Speakon N4			
TourClass Protection:	功放保護功能:	ACL, IGM, Auto Ramp, short circuit, DC voltage, turn-on/off transient, Current inrush, sub/ultrasonic input			
Operating Voltage, 230V/115Vnominal:	工作電壓:	130-265 V / 65-135 V selectable			
Voltage Gain (dB):	電壓增益:	23, 26, 29, 32, 35, 38, 41, 44 dB selectable			
Level adjustment (per CH):	電平調節:	Front-panel potentiometer, 31 position detente from 1 nF to 0 dB			
Installation Standard:	機箱規格:	2 U			
Product Dimensions :	產品尺寸:	480×50×450mm			
N.W./G.W.:	淨重/毛重:	8KG/9.5KG			

MQ SERIES

Class H power Amplifier



MQ-SERIES Class H power Amplifier

DESCRIPTION 產品描述

L-Solution MQ series Class H power amplifier deliver high performance and quality at an astonishingly affordable price. Designed for professional use in touring racks as well as for fixed installation.

Engineered for utmost ease of use, these amps offer connection options XLR inputs for patching in signal s as well as Speakon ports for connecting speaker systems, What's more, their extensive protective circuits ensure reliable, safe operation. applications widely.

鑄之迅MQ系列功放傳承卓越性能、高品質和超乎想象的高性價比。為大型專業演出和固定安裝的音響系統而誕生。為了達到最佳的使用效果，所有的MQ系列開關電源功放都配備有相應的XLR信號輸入和Speakon連接座。最重要的是該系列產品內置有持續保護電路，確保設備長時間的安全、穩定工作

Features 產品特征

- 2/4 Channels input and output
- Available setting independently on each channel
- all-round circuit soft protection
- System gain available setting on 0.775V/1.0V/1.5V Auto temperature control radiation
- Advance heat dissipation system and silent- fan
- 兩/四路音源輸入輸出
- 每路音量獨立調節
- 全功能軟保護
- 0.775V/1.0V/1.5V增益可調,全自動溫度感應散熱滾軸無極風扇、平穩低噪

SPECIFICATIONS 產品參數

Model:	型號	MQ-350	MQ-450	MQ-650	MQ-850	MQ-1000	MQ-1200	MQ-1400
Power RMS @ 8 ohms:	8Ω立體聲功率:	2x350W	2x450W	2x650W	2x850W	2x1000W	2x1200W	2x1400W
Power RMS @ 4 ohms:	4Ω立體聲功率:	2x550W	2x750W	2x950W	2x1150W	2x1250W	2x1450W	2x1650W
Power RMS @ 2 ohms:	2Ω立體聲功率:	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Power Bridged @ 8 ohms:	8Ω橋接功率:	850W	1150W	1450W	1650W	1850W	2150W	2350W
Power Bridged @ 4 ohms:	4Ω橋接功率:	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Frequency Response:	頻率響應:	20Hz-20KHz(+/-0.3dB)						
THD @ 1 kHz:	總諧波失真:	≤0.02%						
S/N Ratio:	信噪比:	>108 dB						
Channel Separation(Crosstalk)@1 kHz:	通道分離度(串音):	>70 dB						
Cooling:	冷卻方式:	Front-to-rear air flow, temperature controlled speed fan						
Signal Input:	信號輸入:	2 x XLR						
Signal Output:	信號輸出:	2 x XLR						
Input impedance:	輸入阻抗:	20K ohms						
Output Connector:	輸出連接器:	4x Speakon N4						
TourClass Protection:	功放保護功能:	ACL, IGM, Auto Ramp, short circuit, DC voltage, turn-on/off transient, Current inrush, sub/Ultrasonic input						
Operating Voltage, 230V/115Vnominal:	工作電壓:	130-265 V / 65-135 V selectable						
Voltage Gain (dB):	電壓增益:	23, 26, 29, 32, 35, 38, 41, 44 dB selectable						
Level adjustment (per CH.):	電平調節:	Front-panel potentiometer, 31 position detente from 1nF to 0 dB						
Installation Standard:	機箱規格:	2 U						
Product Dimensions(mm) :	產品尺寸(mm):	430x88x480	430x88x480	430x88x480	430x88x480	430x88x480	430x88x480	430x88x480
N.W.:	淨重:	14.5Kg	16.9Kg	19.5Kg	22.2Kg	24.3Kg	26.8Kg	30Kg